



## JLN-28160

### SELF-ADHESIVE REINFORCED KRAFT PAPER TAPE

Physical Properties	Standard	Metric	Test Method	
Color	Natural			
Composite Layer Adhesive	Polymeric copolymer			
Water-Activated Adhesive	Hot melt adhesive			
Total Thickness	6.3 mils	0.16 mm	ASTM D-3652	GB/T7125
Peel Strength 90°	90 oz/in	25 N/25mm	ASTM D-3330	GB/T2792
Retention	> 24 h	> 24 h	ASTM D-3654	GB/T4851
Tensile Strength	45 lbs/in	200 N/25mm	ASTM D-3759	GB/T7753
Extensibility	3-5%	3-5%	ASTM D-3759	GB/T7753
Low Temperature	23°F	-5°C	BC/BD-220SE	BC/BD-220SE
High Temperature	140°F	60°C	DHG-9055A	DHG-9055A
Reinforcement	MD	72mm (1-1-1-1-1-1) Fiberglass		
	CD	28mm G150(1-1-1)Fiberglass Diamond Pattern		
base material	Top Ply: 25 lb (40 g/m <sup>2</sup> ) kraft paper			
	Bottom Ply: 25 lb (40 g/m <sup>2</sup> ) kraft paper			

#### Description :

JLN-28160 Packaging Tape is a fast, reliable sealing, economical, pressure-sensitive and self-adhesive packaging kraft tape that improves the efficiency of your packaging line. With strong initial adhesion and a strong seal, the unique gripper rib technology gives this tape better tensile strength than ordinary tape and is less prone to theft.

#### Use Method:

Tear off the tape and use it to seal the top and bottom of the cardboard box. Suitable for all types of cardboard boxes.

#### Storage Condition:

It' s recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 4°C to 26 °C and the humidity shall be between 40% and 50%. Rotate inventory recommended.

#### Shelf Life:

1 years from the date of shipment

The above properties and results obtained refer to the average values of laboratory testing carried out on the samples of JL3 product. JL3 does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. JL3 strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. JL3 assumes no responsibility for any damage or injury sustained as a result of the use of its products.

#### Fujian Jialong Adhesive Tape Co.,Ltd.

No. 11 Xiazhai Road, Jiulong Industrial Park, Hua An Economic Development Zone, Hua An, Zhangzhou, Fujian 363000 China.  
 Tel:+86 596-728-0001  
 info@jl3tape.com  
<http://www.jl3tape.com>

